



## 2 Port VGA, USB 2.0 & Audio Cable KVM Switch

No.: 42342

Switch between 2 computers with VGA connection with only one keyboard, mouse and monitor

### Description

- Control two VGA equipped PCs from a single keyboard, mouse and monitor
- Switch via the unit's push button control, software or keyboard hot keys
- Supports VGA signals, up to 2048x1536
- Integrated cables for quick, hassle-free installation
- 2 Year Warranty

The Lindy 2 Port VGA, USB 2.0 & Audio KVM Switch is a compact solution for providing access and control over two VGA equipped PCs from a single keyboard, mouse and monitor. With integrated cables, this switch can be easily connected directly to the system, with no need for purchasing additional cables and saving time on the installation.

Support for resolutions up to 2048x1536 ensures the optimum image quality, perfect for high graphical content in gaming setups, video editing or dual system control workstations. The audio output port on the main unit also allow users to connect headphones or speakers to add immersive 2CH audio and a microphone, while additional USB peripherals can be integrated with a USB hub.

The KVM switch features multiple switching options including a push button control (with 1.5m cable), hotkey and software switching to provide simple, reliable control for the user, great for both professional and first time users.

*Please note: Software control & hotkey switching are not currently compatible with devices supporting macOS 10.15. This is due to an incompatibility between macOS 10.15 and 32-bit software.*

### Technical details

#### Specifications:

- AV Interface: VGA
- Console Interfaces: USB
- Interface Standard: VGA, USB 2.0
- Maximum Resolution: 2048x1536@30Hz
- HDCP Support: -
- Supported Audio: Analogue Stereo
- Separate Audio Ports: 2 x 3.5mm (Female)
- Serial Interface: -
- Console Number: 1
- Max Number PC/Server: 2

- Cascadable: -
- Switching Method: Push Button, Hotkey Switching & Software
- 19" Rack Mountable: -
- Special Features: Supports USB 2.0 Hubs and Device Sharing, Active LED Indicators

**Connectors:**

- Console Interfaces: VGA [Female], USB 2.0 Type A [Female], 2 x 3.5mm [Female]
- PC/Server Interfaces: 2 x VGA [Male], USB 2.0 Type A [Male], 2 x 3.5mm [Male] 1.2m Integrated Cables
- Other Interfaces: -
- Power: -

**Physical properties:**

- Dimensions (approx.) WxDxH: 87x25x58,78mm [3.43x0.98x2.31in]
- Housing Material: Plastic
- Net Weight: 0.46kg [1.01lb]
- Operating Temperature: 0°C - 50°C [32°F - 122°F]
- Storage Temperature: -20°C - 60°C [-4°F - 140°F]
- Humidity: 0~90% RH [non-condensing]
- Power Requirements: 5V
- Colour: Black

**Miscellaneous:**

- Packaging Type: Carton box
- Packaging Dimensions: 160x60x210mm [6.3x2.36x8.27in]
- Gross Weight: 0.6kg [1.32lb]
- Warranty [Years]: 2
- Certificated: CE, FCC, RoHS & REACH

**Package content:**

- VGA KVM Switch
- Lindy Manual

**Purchasing information:**

- No.: 42342
- EAN: 4002888423427